

## FEA18RCZ H1794-08

The FEA18RCZ is an 18cm (6.5") full range driver offering excellent efficiency and extended bandwidth in a more compact package.

A blue-gray paper cone with papyrus fibres, and a high frequency cone directly coupled to the voice coil set the air in motion. The flexible surround is made from a low-loss rubber material with minimal damping properties.

The large spider provides low mechaincal resistance, and offers excellent stiffness linearity. A heat resistant, non conductive glass fiber coil former allows a high mechanical Q-factor of the moving system.

A large ferrite ring magnet offers a high magnetic gap flux in a cost efficient way. The pole piece is prolonged forwards and equipped with a long copper cap to ensure excellent linearity in the force factor and coil inductance.

A stiff and stable injection moulded zinc chassis keeps the critical components in perfect alignment. Large windows in the chassis both above and below the spider reduce sound reflexion, air flow noise and cavity resonance to a minimum.







The frequency responses above show measured free field sound pressure in 0, 30, and 60 degree angles using a 12L closed box. Input 2.83 V<sub>KMS</sub>, microphone distance 0.5m, normalized to SPL 1m. The dotted line is a calculated response in infinite baffle based on the parameters given for this specific driver. The impedance is measured in free air without baffle using a 2V sine signal.

| a _ t = t = t = t = t = t = t = t = t = t |               |                                  |                     |
|---|---------------|----------------------------------|---------------------|
| Nominal Impedance                         | 8 Ohms        | Voice Coil Resistance            | 5.7 Ohms            |
| Recommended Frequency Range               | 45 - 20000 Hz | Voice Coil Inductance            | 0.49 mH             |
| Short Term Power Handling *               | 110 W         | Force Factor                     | 6.6 N/A             |
| Long Term Power Handling *                | 40 W          | Free Air Resonance               | 42 Hz               |
| Characteristic Sensitivity (2,83V, 1m)    | 89.7 dB       | Moving Mass inc. air (Mms)       | 12.1 g              |
| Voice Coil Diameter                       | 26 mm         | Suspension Compliance            | 1.19 mm/N           |
| Voice Coil Height                         | 12 mm         | Suspension Mechanical Resistance | 0.51 Ns/m           |
| Air Gap Height                            | 6 mm          | Effective Piston Area            | 136 cm <sup>2</sup> |
| Linear Coil Travel (p-p)                  | 6 mm          | VAS                              | 31 Litres           |
| Maximum Coil Travel (p-p)                 | 14 mm         | QMS                              | 6.29                |
| Magnetic Gap Flux Density                 | 1.1 T         | QES                              | 0.42                |
| Magnet Weight                             | 0.6 kg        | QTS                              | 0.39                |
| Total Weight                              | 1.8 kg        |                                  |                     |
|   |               |                                  |                     |

Feb 2017

\*IEC 268-5 SEAS reserves the right to change technical data

RoHS compliant product