





# 10PS26-16

Rev: 1

Frequency Response



Impedance



## Specifications

Nominal Diameter	<b>10"</b>
Nominal Impedance	<b>16 Ω</b>
Minimum Impedance	<b>10.1 Ω</b>
Power Handling	
Nominal <sup>1</sup>	<b>350 W</b>
Continuous Program <sup>2</sup>	<b>700 W</b>
Sensitivity (1W/1m) <sup>3</sup>	<b>95 dB</b>
Frequency Range	<b>Fs to 4000 Hz</b>
Voice Coil Diameter	<b>76,00 mm</b>
Winding Material	<b>Aluminium</b>
Former Material	<b>Kapton</b>
Winding Depth	<b>18,50 mm</b>
Magnetic Gap Depth	<b>10.5 mm</b>
Flux Density	<b>1.05 T</b>
Surround Material	<b>PolyCotton</b>
Surround Shape	<b>Double Roll</b>
Spider Material	<b>PolyCotton</b>
Magnet Material	<b>Ceramic</b>
Cone Material	<b>Paper</b>
Water Proof Front Side (WP)	<input type="checkbox"/>
Water Proof Both Sides (TWP)	<input type="checkbox"/>
Epoxy Treatment	<input checked="" type="checkbox"/>
Demodulation Ring	<input type="checkbox"/>
Shorting Copper Ring	<input checked="" type="checkbox"/>
Double Spider	<input type="checkbox"/>
Vented Gap	<input type="checkbox"/>

31/03/2005

## Thiele & Small Parameters<sup>4</sup>

Fs	<b>54 Hz</b>
Re	<b>10,0 Ω</b>
Qes	<b>0,37</b>
Qms	<b>5,00</b>
Qts	<b>0,34</b>
Vas	<b>28,0 dm<sup>3</sup></b>
Sd	<b>320 cm<sup>2</sup></b>
η <sub>0</sub>	<b>1,26 %</b>
Xmax	<b>8,0 mm</b>
Xvar	<b>8,00 mm</b>
Mms	<b>45,0 g</b>
Bl	<b>20,10 Txm</b>
Le	<b>2,40 mH</b>
Cms	<b>195,0 μm/N</b>

## Mounting Information

Overall Diameter	<b>261 mm ( 10,2 in )</b>
Bolt Circle Diameter	<b>245 mm ( 9,6 in )</b>
Baffle Cutout Diameter	<b>230 mm ( 8,8 in )</b>
Depth	<b>123 mm ( 4.8 in )</b>
Flange / Gasket Thickness	<b>17 mm ( 2/3 in )</b>
Net Weight	<b>6 kg ( 13.2 lb )</b>

(1) A.E.S. Standard

(2) Power on Continuous Program is defined as 3 dB greater than the Nominal rating.

(3) Applied RMS Voltage is set to 4V for 16 ohms Nominal Impedance. Average SPL from 400 to 400 Hz

(4) Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.