


15PLB76

LF Drivers - 15.0 Inches









- 800 W continuous program power capacity76 mm (3 in) copper voice coil
- 40 2000 Hz response
- 100 dB sensitivity



LF Drivers- 15.0 Inches





SPECIFICATIONS

Nominal Diameter	380 mm (15.0 in)
Nominal Impedance	8 Ω
Minimum Impedance	6.2 Ω
Nominal Power Handling ¹	400 W
Continuous Power Handling ²	800 W
Sensitivity ³	100.0 dB
Frequency Range	40 - 2000 Hz
Voice Coil Diameter	76 mm (3.0 in)
Winding Material	Copper
Former Material	Glass Fibre
Winding Depth	16.0 mm (0.62 in)
Magnetic Gap Depth	11.0 mm (0.4 in)
Flux Density	1.15 T

DESIGN

Surround Shape	Triple Roi
Cone Shape	Exponentia
Magnet Material	Ferrite
Spider	Single
Pole Design	T-Pole
Woofer Cone Treatment TWP \	Waterproof Both Sides
Recommended Enclosure	100.0 dm ³ (3.53 ft ³)
Recommended Tuning	50 Hz

PARAMETERS⁴

Resonance Frequency	42 Hz
Re	5.0 Ω
Qes	0.26
Qms	5.9
Qts	0.25
Vas	164.0 dm ³ (5.8 ft ³)
Sd	855.0 cm ² (132.5 in ²)
ηο	4.5 %
Xmax	5.0 mm
Maximum Excursion	8.0 mm
Mms	88.0 g
Bl	22.1 Txm
Le	1.3 mH
EBP	161 Hz

MOUNTING AND SHIPPING INFO

Overall Diameter	393 mm (15.5 in)	
Bolt Circle Diameter	374 mm (14.7 in)	
Baffle Cutout Diameter	354.0 mm (13.9 in)	
Depth	169 mm (6.65 in)	
Flange and Gasket Thicknes	SS 16 mm (0.62 in)	
Air Volume Occupied by Driver $$5.2\ dm^{3}\ (0.18\ ft^{3})$$		
Net Weight	8.5 kg (18.7 lb)	
Shipping Units	1	
Shipping Weight	9.8 kg (21.61 lb)	
Shipping Box		

SERVICE KIT

RCK15PLB768

- 2 hours test made with continuous pink noise signal within the range Fs-10Fs. Power calculated on rated nominal impedance. Loudspeaker in free air.
 Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
 Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
 Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.