



DCX50

HF Drivers - 2 Inches

160 W continuous program power capacity
 2' horn throat diameter
 400 - 16000 Hz response
 108.5 dB sensitivity
 Neodymium magnet assembly
 Time coherent coaxial design

Specification

Throat Diameter	50 mm (2 in)
Nominal Impedance	8 ohm
Minimum Impedance	8 MF - 7 HF ohm
Frequency Range	0.4 - 16 Hz
Recommended Crossover	0.4 kHz

MF UNIT

Sensitivity (1W/1m)	108.5 dB
Continuous Power Handling	160 W
Nominal Power Handling (AES)	80 W
Voice Coil Diameter	51 mm (2 in)
Winding Material	Aluminium
Diaphragm material	Composite

HF UNIT

Sensitivity (1W/1m)	108.5 dB
Nominal Power Handling (AES)	20 W
Continuous Power Handling	40 W
Voice Coil Diameter	32 mm (1.2 in)
Winding Material	Aluminium
Diaphragm material	Mylar

Mounting & Shipping

Overall Diameter	152 mm (6 in)
Depth	108 mm (4.25 in)
Net Weight	3.3 kg (7.3 lb)
Shipping Weight	3.5 kg (7.7 lb)
Shipping Box	170x170x140 mm (6.7x6.7x5.5 in)

Replacement Diaphragm MF	MMDDCX08
Replacement Diaphragm HF	MMDTWDCX8