

Pro**HIGH FREQUENCY COMPRESSION UNITS
UNIDADES DE COMPRESION DE ALTA FRECUENCIA****NEW****CP 850/Nd****CP 600/Ti****CP 800/Ti****NEW****CP 360/K****CP 350/Ti**

MODEL	CP 850/Nd	CP 800/Ti	CP 600/Ti	CP 360/K	CP 350/Ti
Power Capacity (RMS)	60 w / 500 Hz 125 w / 1.2 kHz	60 w / 500 Hz 125 w / 1.2 kHz	60 w / 1 kHz 100 w / 2 kHz	35 w / 1 kHz 50 w / 2 kHz	40 w / 1 kHz 60 w / 2 kHz
Sensitivity 1w @ 1m	114 dB	112 dB	110 dB	108 dB	104 dB
Frequency Range	500 • 20000 Hz	500 • 20000 Hz	600 • 17000 Hz	900 • 20000 Hz	800 • 20000 Hz
Lowest Cross. Frequency	500 Hz	500 Hz	600 Hz	1200 Hz	1000 Hz
Voice Coil Diameter	100 mm • 4"	100 mm • 4"	72 mm • 2" 3/4	44.4 mm • 1" 3/4	44.4 mm • 1" 3/4
Throat Diameter	49 mm • 2"	49 mm • 2"	49 mm • 2"	25 mm • 1"	25 mm • 1"
Diaphragm material	Titanium	Titanium	Titanium	Kapton	Titanium
Magnet material	Neodymium	Ferrite	Ferrite	Ferrite	Ferrite
Overall Diameter	165 mm	228 mm	208 mm	144 mm	140 mm
Depth	110 mm	117 mm	70 mm	67 mm	65 mm