



12PR310

12" - 300 W - 99 dB

NOMINAL SPECIFICATIONS

Nominal Diameter	300 mm (12 in)
Overall Diameter	316 mm (12.44 in)
Bolt Circle Diameter	298.5 mm (11.75 in)
Baffle Cutout Diameter	282 mm (11.10 in)
Depth	135 mm (5.31 in)
Flange and gasket Thickness	12 mm (0.47 in)
Net Weight	4.3 kg (9.5 lb)
Shipping Box	350 x 346 x 190 mm
(Single Carton Box)	(13.8 x 13.6 x 7.5 in)
Shipping Weight	5 kg (11.0 lb)

TECHNICAL PARAMETERS

Nominal Impedance	8 Ω
Minimum Impedance	6.7 Ω
AES Power Handling (1)	300 W
Maximum Power Handling (4)	600 W
Sensitivity (1W/1m)	99 dB
Frequency Range	50 ÷ 4000 Hz
Voice Coil Diameter	65 mm (2.56 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	12.5 mm (0.49 in)
Magnetic Gap Depth	8 mm (0.31 in)
Flux Density	1.2 T
Magnet	Ferrite Ring
Basket Material	Aluminum
Demodulation	No
Cone Surround (5)	M-Roll
NET Air Volume filled by Loudspeaker	1.9 dm ³ (0.067 ft ³)
Spider Profile	1x variable height waves

THIELE & SMALL PARAMETERS

Fs	54 Hz
Re	5.4 Ω
Qes	0.41
Qms	11.6
Qts	0.40
Vas	62.8 dm ³ (2.22 ft ³)
Sd	489 cm ² (75.80 in ²)
Xmax (2)	4.92 mm
Xdamage (3)	15.25 mm
Mms	46.9 g
Bl	14.4 N/A
Le	0.61 mH
Mmd	40.1 g
Cms	0.18 mm/N
Rms	1.37 kg/s
η _o (Eta Zero)	2.32 %
EBP	132 Hz

NOTE:

- 2 Hours Test According to AES 2-1984 Rev. 2003
- $X_{max} = [(Winding\ Depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth / 3)$
- Maximum excursion before permanent damage
- Maximum power is defined as 3dB greater than nominal power
- Treated Polycotton

