



15FH520

15" - 600 W - 97 dB

NOMINAL SPECIFICATIONS

Nominal Diameter	380 mm (15 in)
Overall Diameter	393 mm (15.47 in)
Bolt Circle Diameter	374 mm (14.72 in)
Baffle Cutout Diameter	356 mm (14.02 in)
Depth	181.3 mm (7.14 in)
Flange and gasket Thickness	13.7 mm (0.54 in)
Net Weight	4.6 kg (10.1 lb)
Shipping Box	430 x 427 x 236 mm
(Single Carton Box)	(16.9 x 16.8 x 9.3 in)
Shipping Weight	5.7 kg (12.6 lb)

TECHNICAL PARAMETERS

Nominal Impedance	4 Ω
Minimum Impedance	3.2 Ω
AES Power Handling (1)	600 W
Maximum Power Handling (4)	1200 W
Sensitivity (1W/1m)	97 dB
Frequency Range	40 ÷ 3150 Hz
Voice Coil Diameter	77 mm (3 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	22.3 mm (0.88 in)
Magnetic Gap Depth	12 mm (0.47 in)
Flux Density	1.1 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround (5)	Triple Roll
NET Air Volume filled by Loudspeaker	3.4 dm ³ (0.120 ft ³)
Spider Profile	1x variable height waves

THIELE & SMALL PARAMETERS

Fs	38 Hz
Re	2.7 Ω
Qes	0.35
Qms	9.0
Qts	0.34
Vas	146.2 dm ³ (5.16 ft ³)
Sd	813 cm ² (126.02 in ²)
Xmax (2)	9.15 mm
Xdamage (3)	15.6 mm
Mms	114.7 g
Bl	14.3 N/A
Le	0.68 mH
Mmd	101.6 g
Cms	0.16 mm/N
Rms	3 kg/s
η _o (Eta Zero)	2.10 %
EBP	109 Hz

NOTE:

- 2 Hours Test According to AES 2-1984 Rev. 2003
- Xmax = [(Winding Depth - magnetic gap depth)/2] + (magnetic gap depth / 3)
- Maximum excursion before permanent damage
- Maximum power is defined as 3dB greater than nominal power
- Treated Polycotton

