



NOMINAL SPECIFICATIONS

Throat Diameter	25,4 mm (1 in)
Overall Diameter	121 mm (4.76 in)
180° Mounting Holes Diameter (2xM6)	76 mm (2.99 in)
Depth	75.4 mm (2.97 in)
Net Weight	2.45 Kg (5.40 lb)
Shipping Box	200x175x90 mm (7.87x6.89x3.54 in)
Shipping Weight	2.6 Kg (5.73 lb)

TECHNICAL PARAMETERS

Nominal Impedance	8 ohm
Minimum Impedance	6.6 ohm
AES Power Handling *	70 W
Maximum Power Handling **	140 W
Minimum Crossover Frequency ***	1 kHz
Sensitivity (1W/1m) ****	109 dB
Frequency Range	0.8÷20 kHz
Voice Coil Diameter	45 mm (1.73 in)
Winding Material	Al
Former Material	Kapton
Diaphragm Material	Ketone Polymer
Diaphragm Shape	Annular
Winding Depth	2.3 mm (0.09 in)
Magnetic Gap Depth	2.6 mm (0.10 in)
Flux Density	1.9 T
Re	5.4 ohm
Phase Plug Design	Annular

NOTES

Driver mounted on a 1" 50° x 40° horn

(* Test made for 2 hours with Pink Noise signal (6 dB Crest Factor) from minimum crossover frequency. Power calculated on rated minimum impedance. Driver mounted on aluminium horn.

(**) Maximum power is defined as 3dB greater than nominal power.

(***) 12 dB/oct or higher slope high-pass filter

(****) Averaged within the frequency range

CURVES



