



W8N8-150

8" - 150 W - 93 dB

NOMINAL SPECIFICATIONS

Nominal Diameter	200 mm (8 in)
Overall Diameter	223.75/207.9 mm (8.81/8.18 in)
Bolt Circle Diameter	210 mm (8.27 in)
Baffle Cutout Diameter	183 mm (7.20 in)
Depth	116.7 mm (4.59 in)
Flange and gasket Thickness	10.7 mm (0.42 in)
Net Weight	1.7 kg (3.7 lb)
Shipping Box	235 x 235 x 155 mm
(Single Carton Box)	(9.3 x 9.3 x 6.1 in)
Shipping Weight	2.6 kg (5.7 lb)

TECHNICAL PARAMETERS

Nominal Impedance	16 Ω
Minimum Impedance	12.7 Ω
AES Power Handling (1)	150 W
Maximum Power Handling (4)	300 W
Sensitivity (1W/1m)	93 dB
Frequency Range	80 ÷ 6300 Hz
Voice Coil Diameter	52 mm (2 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	13.7 mm (0.54 in)
Magnetic Gap Depth	8 mm (0.31 in)
Flux Density	1 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	No
Cone Surround (5)	M-Roll
NET Air Volume filled by Loudspeaker	1 dm ³ (0.035 ft ³)
Spider Profile	1x variable height waves

THIELE & SMALL PARAMETERS

Fs	76 Hz
Re	11.8 Ω
Qes	0.88
Qms	19.5
Qts	0.85
Vas	11.1 dm ³ (0.39 ft ³)
Sd	206 cm ² (31.93 in ²)
Xmax (2)	5.52 mm
Xdamage (3)	12 mm
Mms	23.8 g
Bl	12.3 N/A
Le	0.9 mH
Mmd	22.8 g
Cms	0.18 mm/N
Rms	0.58 kg/s
η _o (Eta Zero)	0.53 %
EBP	86 Hz

NOTE:

- 2 Hours Test According to AES 2-1984 Rev. 2003
- Xmax = [(Winding Depth - magnetic gap depth)/2] + (magnetic gap depth / 3)
- Maximum excursion before permanent damage
- Maximum power is defined as 3dB greater than nominal power
- Treated Polycotton

