



## 2002

Nominal Diameter	8" / 20 cm
Rated Impedance	8 Ω
Sensitivity	92 dB SPL
Power Handling Capacity	120 W AES
SPL max (continuous)	109 dB SPL
Usable frequency range	60 - 4000 Hz
Speaker net mass	2,5 kg

## 8 inches low-mid driver



### Architecture highlights :

- Natural convection Intercooler System
- Double side coated diaphragm (Tropical withstanding)
- High compliance double half-roll Fabric Surround

### Motor architecture

Magnet material	-	Fe
Voice coil diameter	mm	38
Voice coil length	mm	14
Air gap height	mm	6

### Typical characteristics


Rated impedance	Z	Ω	8
Half space sensitivity (1W@1m)	-	dB SPL	92,0
Usable freq. range	-	Hz	60 - 4000
Power handling capacity (AES)	-	W	120
Max Sound Pressure Level	SPL <sub>max</sub>	dB SPL	109
Min. impedance modulus	Z <sub>min</sub>	Ω@Hz	6.1@320
Voice-coil inductance @ 1kHz	Le <sub>1k</sub>	mH	0,516
Voice-coil inductance @ 10kHz	Le <sub>10k</sub>	mH	0,303
BL product	BL	N/A	9,5
Moving mass	Mms	kg	0,021

### Thiele-Small parameters

Resonance frequency	Fs	Hz	77 (±11)
DC Resistance	Re	Ω	5.4 (±0.5)
Mechanical quality factor	Qms	1	4,07
Electrical quality factor	Qes	1	0,61
Total quality factor	Qts	1	0,53
Suspension compliance	Cms	10 <sup>-6</sup> .m/N	200
Effective piston area	Sd	m <sup>2</sup>	0,0219
Equivalent Cas air load	Vas	m <sup>3</sup>	0,0136
Max linear excursion	Xmax	mm	± 5,5
Linear displacement volume	Vd	10 <sup>-3</sup> .m <sup>3</sup>	0,1205
Reference efficiency	η <sub>0</sub>	%	1,0
Unity load volume	Vas.Qts <sup>2</sup>	10 <sup>-3</sup> .m <sup>3</sup>	3,8

### Absolute maximum ratings

Short term max. input voltage	Vmax	V	60
Max. excursion before damage	Xdam	mm	± 10,0
Ambient operating temperature	Ta	°C	-10 to +50
Storage temperature		°C	-20 to +70
Environmental withstanding			Tropical



### Mounting information

Air volume occupied by the driver	10 <sup>-3</sup> .m <sup>3</sup>	0,61
Speaker net mass	kg	2,5
Baffle cut-out diameter (front mounting)	mm	185,0
Bolt number & Metric diameter	-	4x M5
Bolt circle diameter	mm	217,0
Max overall dimension (on ears)	mm	234,0
Max overall dimension (out of ears)	mm	205,0
Flange height	mm	9,5
Max magnet diameter	mm	117,5
Max depth (front mounting)	mm	84,0
Recommended reflex box	Lts / Hz	20L / 65Hz
Electrical connection		6.3x0.8 Faston