

CDK455

DRIVER



Rev. C Last update: 19/02/2024



TECHNICAL SPECIFICATIONS

General specifications	Exit Throat Diameter:	1.0 inch / 25 mm
	Related Impedance:	8 ohm
	Program Power (watt):	140 W
	Power handling capacity (watt):	70 W
	Sensitivity:	109 dB
	Frequency range:	1200 - 20000 Hz
	Suspension Design:	Flat
	Minimum Impedance (ohm):	6.50 ohm
	Voice Coil Diameter:	1.75 inch / 44 mm
	Voice Coil Former Design:	Straight - Kapton
	Number of layers:	1
	Kind of layers:	outside
	Flux Density:	1.5 T
	Phase Plug Design:	2 slot
Thiele - small parameters	BI factor (BI) (T x m):	5.85 T x m
Mounting information	Overall diameter:	102 mm / 4.02 inches
	Overall height:	47 mm / 1.85 inches
	Mounting:	4 x 6 mm threaded holes at 90°
Standard compliance	Safety agency:	CE compliant
Size	Weight:	1.23 kg / 2.71 lbs
Shipping information	Package Height:	74 mm / 2.91 inches
	Package Width:	122 mm / 4.8 inches
	Package Depth:	123 mm / 4.84 inches

PART NUMBER

· 15100031

CDK455

